

Product Features

- Load Sharing
- Load Shedding
- Built in 20kW Load Bank
- Wheels Interchangeable with HMMWV
- Front Fuel Filler and Gauge in Containment Box
- Fuel Select Switch (Trailer or Auxiliary)
- Quick Connect Auxiliary Fuel Fittings for External Fuel Source • Engine Fluid Drains Ported to Frame
- Automatic Shutdowns (Low Oil Pressure, High Coolant temperature)
- 15 1/2" Minimum Ground Clearance
- Fuel Consumption 5.5 GPH at Full Load

Specifications

60kW HMMWV Towable Trailer

Engine	4 cylinder turbo charged diesel
Generator Output	120/208 VAC 3-Phase 60-Hz; Rated 60kW at 10,000 ft & 50°C
System Weight	4,155 lbs. Without fuel
Dimensions	85"W x 94"H x 160"L
Mobility	Department of Transportation & Air Certified, roll-on/roll-off C-130, C-141, C-5, & C-17 HMMWV towable
Operating Environment	-40°F to 125°F (Fuel-fired coolant heater)
Noise	Less than 70 db at 25 ft.

OPTIONS:

- Composite Run Flats
- Fuel Fired Coolant Heater Starts at 40° Below Without External Sources of Power
- Third Wheel at Tongue (rotates vertical for ramp crest)
- Dual Wall Fuel Tank
- Available in Digital Control with Remote Monitoring Digital Units are Power Grid capable.

