



This complete audio system includes an amp, mixer, power distribution panel, speakers, microphone, storage drawer and additional cables all in a central unit. Component design allows the user to adapt the system as required. Maximum portability, easy setup and adjustment combined with excellent audio quality and reliability make this system both versatile and convenient. The system is contained in a shock-mounted, weather-resistant case.

## KEY FEATURES

- QSC GX Series amplifier
- Amplifier binding posts support all other speaker wiring systems
- 12 channel mixer
- Power panel has dual LED pop-out lights with dim control knob
- USB receptacle on front panel for lighting up rack
- System speakers feature a weatherproof design with Teflon® sealed internal cabinetry and driver
- Weather-proof transit case and three (3) 50' (15.24 m) high-quality speaker cables
- Microphone has built-in spherical filter to minimize wind and breath "pop" noise
- One (1) 50' (15.24 m) XLR shielded microphone cable and one RCA to 1/8" (3 mm) cable included



## SHELTER AUDIO SYSTEM SPECIFICATIONS

### Ordering information

HDT part number	40SA01
NSN	5975-01-C16-1316
GSA	

### Amplifier/Mixer

Dimensions (L x W x H)	28.25" x 29" x 26.25"	71.75 x 73.66 x 66.68 cm
Weight	118 lbs	53.52 kg

### Amplifier

Power	300 watts per channel at 8 ohms
Safety features	GuardRail™ automatically protects the amplifier and loudspeakers from damage due to temperature rise or overdrive
Inputs	XLR, ¼" (6.35 mm) TRS and phono input connectors for compatibility with any source
Outputs	Speakon® combo accepts, ¼" (6.35 mm) (TS) plugs or Speakon 2-pole and 4-pole plugs (connects 2 poles only).

### Mixer

Inputs	8 high-gain mic/line (XLR and ¼" (6.35 mm) balanced) inputs with phantom power 2 stereo balanced ¼" (6.35 mm) line inputs
Outputs	2 aux sends (pre- and post-fader), Stereo aux return Eight ¼" (6.35-mm) inserts 2-track stereo RCA in and out Separate ¼" (6.35-mm) balanced main and monitor outs Front-panel headphone out

### Power distribution panel

Rear	7 protected switched A/C grounded outlets 1 A/C unswitched outlet
Front	1 A/C outlet switched on front of panel
Incoming line voltage meter	15A per outlet/20A protection breaker button on front panel
Protection	20A breaker

### Speakers

Power handling	120 watts peak
Frequency response	35Hz – 19kHz 4-6 ohms and 25V 70V switchable for commercial installations
Dimensions (L x W x H)	8.5" x 11.75" x 7.5"                      21.59 x 29.85 x 19.05 cm

### HDT Global

30500 Aurora Road Suite 100  
Solon, OH 44139 USA  
P 800.969.8527 / 540.887.4700  
sales@hdtglobal.com

THIS COMMODITY, TECHNOLOGY OR SOFTWARE IS SUBJECT TO THE EXPORT ADMINISTRATION REGULATIONS (EAR), 15 CFR 730-774, OF THE UNITED STATES OF AMERICA.

Revision 1 08-13 01-03-01-0148