



**Product Features**

**Trailer:**

- 15.5" (39.4 cm) ground clearance
- Three removable side barriers
- Recessed cargo tie-downs in deck
- Cargo tarpaulin cover
- Supply and return fuel lines included
- Wheels interchangeable with HMMWV
- Fuel dispensing system with nozzle, 24VDC
- Front-fill fuel tank with fuel gauge in containment box. Quick connection to generator set aux supply.

**Options:**

- Composite run flats
- Third wheel at tongue (rotates vertical for ramp crest)
- Dual wall fuel tank

**ECU:**

- Ozone friendly R407C refrigerant
- Hot gas by-pass
- In-rush current limited
- 3,200 cfm (5437 m<sup>3</sup>/h)
- Easy-latch connections to air duct transitions
- Two 12" (30.4 cm) supply duct transitions
- One 18" (45.7 cm) return air duct transition

**Options:**

- Other duct configurations available
- Remote thermostat and controls



**Specifications Cargo ECU Trailer**

<b>Ordering information</b>		
HDT part number	?	
NSN	?	
<b>Physical characteristics</b>		
H x W x L	100" x 85" x 164"	254 x 215.9 x 416.6 cm
Height w/o bows	80"	203.2 cm
ECU	49.5" x 34.5" x 57"	125.7 x 87.6 x 144.8 cm
GVWR	5500 lbs	2494.8 kg
System weight (dry)	2530 lbs	1147.6 kg
<b>Fuel</b>		
Fuel capacity	85 gallons	321.76 liters
<b>Power</b>		
	15kW 208 VAC, 60HZ	
<b>ECU</b>		
Input	60 Amp MS90558C32412P Inlet	
Cooling	96,000 BTU/h	28.1 kW
Heating	46,000 BTU/h	13.5 kW
<b>Mobility</b>		
	Department of Transportation Compliant. Roll-on/roll-off C-130, C-141, C-5 & C-17. HMMWV towable. 3 in. diameter Lunette.	

HDT Engineered Technologies  
30500 Aurora Road, Suite 100  
Solon, OH 44139 USA

P 800.969.8527  
F 440.248.1691  
sales@hdtglobal.com

**Engineered to move with you**

[hdtglobal.com](http://hdtglobal.com)

Revision 01 - 05-20-2011