

HDT LED SHELTER LIGHTING

Long Life, Low Power Consumption Lighting

HDT[®]
GLOBAL



EMI Protected LED Shelter Lights

EMI (electromagnetic interference) hardened lights will not compromise peripheral electronics, communication equipment, computers or medical equipment.

KEY FEATURES

- Black out mode greatly reduces visible signature
- Will not trip GFCI when connecting over 30 lights, exceeding military specification of 12-light connectivity
- On/off switches for independent light operation
- Light output and dispersion comparable to fluorescent lighting with significantly less energy consumption
- Push-button dimming saves more power
- Interoperable with Jameson's fluorescent string lights
- Compliant with MIL-STD-461, RE102 and CE102 for Army Ground Field Hospitals, Command Centers, Force Provider, BEAR Base
- International plug configurations available



HDT LED SHELTER LIGHTING

Long Life, Low Power Consumption Lighting



EMI PROTECTED LED LIGHTING SPECIFICATIONS

Ordering information	1 Stringable Light	2 Stringable Lights Carry Bag	2 Stringable Lights Transport Case	3 Stringable Lights Transport Case	4 Stringable Lights Transport Case
Blue Blackout					
HDT Part Number	69EL004BL	69EL004-2BGBl	69EL004-2PKBl	69EL004-3PKBl	69EL004-4PKBl
NSN	N/A	N/A	N/A	N/A	N/A
On GSA Contract	N/A	N/A	N/A	N/A	N/A
Red Blackout					
HDT Part Number	31-400R	31-B-400R	N/A	N/A	31-MC-400R
NSN	N/A	N/A	N/A	N/A	N/A
On GSA Contract	N/A	N/A	N/A	N/A	N/A
Accessories	Hanging Straps	Hanging Straps Carry Bag	Hanging Straps Transport Case	Hanging Straps Transport Case	Hanging Straps, Transport Case
Physical characteristics (per light)					
L x D*	32.25" x 3.75"	32.25" x 3.75"	32.25" x 3.75"	32.25" x 3.75"	32.25" x 3.75"
	81.9 x 9.5 cm	81.9 x 9.5 cm	81.9 x 9.5 cm	81.9 x 9.5 cm	81.9 x 9.5 cm
Weight	4.7 lbs	4.7 lbs	4.7 lbs	4.7 lbs	4.7 lbs
	2.1 kg	2.1 kg	2.1 kg	2.1 kg	2.1 kg
Electrical voltage	100-240 VAC, 50/60 Hz	100-240 VAC, 50/60 Hz	100-240 VAC, 50/60 Hz	100-240 VAC, 50/60 Hz	100-240 VAC, 50/60 Hz

* Length without cords and major diameter, with cords 120" (304.8 cm) diameter and a minor diameter of 2.6" (6.6 cm)

HDT Global

30500 Aurora Road Suite 100
Solon, OH 44139 USA
P 800.969.8527 / 540.887.4700
sales@hdtglobal.com

Revision 1 05-16 01-03-01-0359