

ULTRA-LITE 49-INCH FLAT SCREEN AND LIFT CASE

Complete Solution for Mobile Display Transport and Use



The HDT Ultra-Lite 49-inch Flat Screen and Lift Case are a complete solution for moving, storing and viewing digital displays. The 49-inch LG commercial series display has a sleek, practical design with a slim bezel and depth for optimum space utilization while offering viewers crisp, high-definition images. The display features conformal coating to increase circuit board reliability by protecting against dust, iron powder, humidity and other harsh conditions.

The lift and storage case provides an innovative, cost-effective solution to transport and use the flat-screen monitor. The display can be set up by one person and is ready for use in less than five minutes. The case utilizes an innovative shock-mounted lift mechanism, which gently raises the flat screen monitor out of the protective case and into viewing position. The display can be used horizontally or vertically and can be adjusted for viewing heights from 61" to 73". The entire assembly can easily be moved by one person and doesn't require electrical power for set-up.

KEY FEATURES

- LG SE3DD Series commercial display mounted on a rotating mounting bracket
- Display's diverse interface allows you to connect more than one device for optimal use
- Display stores vertically in the case for minimal footprint
- Shock-mounted lift mechanism
- Stable and portable with four 3" dual casters
- Side glides to easily move case when tipped on edge during transport
- Rear access port for electric cables
- Interior mounted (multi-outlet) power strip with 15-foot cable
- Accessory bag for remotes, cords and cables
- Plastic cavity covers conceal the inside of the case

ULTRA-LITE 49-INCH FLAT SCREEN AND LIFT CASE

Complete Solution for Mobile Display Transport and Use



ULTRA-LITE 49-INCH FLAT SCREEN AND LIFT CASE SPECIFICATIONS

Ordering information

HDT part number	106-H015396 Milcoat Tan
NSN	N/A
On GSA Contract	N/A

Monitor

	49" LG SE3DD Series display	
Size (L x W x H)	43.4" x 25.1" x 1.5"	1,102.2 x 638.5 x 38.6 mm
Resolution	1,920 x 1,080 (FHD)	
Weight (display only)	30.6 lbs	13.9 kg
Input	HDMI (2), Analog (RGB), Audio, USB	
Output	External speaker out	
Power	100-240V~, 50/60Hz	
Power consumption	65W	

Monitor accessories

Remote controller (include battery 2ea), power cord, QSG, RGB cable, regulation book, IR receiver

Environmental Conditions

Operating temperature range	32° to 104° F	0° to 40° C
Operating humidity range	10% to 80%	10% to 80%

Case

Packed size (L x W x H)	30" x 17.5" x 54"	76.2 x 44.5 x 137.2 cm
Weight (case only)	128 lbs	58.1 kg
Locking casters	Four 3" double casters	Four 7.6 cm double casters

Total Weight

158.6 lbs	72 kg
-----------	-------

Products, product specifications and data are subject to change without notice to improve reliability, function, and/or design. Please contact Customer Service at 800.969.8527 for the most up-to-date product information.



HDT Global

30500 Aurora Road, Suite 100
 Solon, OH 44139 USA
 P 800.969.8527 / 540.887.4700
 sales@hdtglobal.com