





The HDT 1SD Rapid Setup Command And Control Display provides eyes-on command and control access to mission-critical data. The 1SD is ideal for displaying C4ISR computer applications, surveillance feeds, UAV ops and mission planning. Deploy as a single unit or place multiple systems side-by-side to create a larger C2 picture.

The 1SD is a rugged display solution that sets up in minutes. By providing a near limitless upgrade platform for projectors and screen sizes, this durable display system is designed to accommodate the latest projection technologies.

Paired with an optional video distribution unit, the HDT 1SD can switch between video sources and can support quint-screen images.

KEY FEATURES

- Rugged, lightweight
- Operational in minutes
- Ultra-bright, high-res images
- Deploy as a single unit or side-by-side for a larger, C2 wall
- Supported input devices include PCs / Macs, smart phones, broadcast receivers, surveillance feeds, tablets, DVD / Blu-Ray players





Ordering Inform	nation				
Part number	106-1SD-1750-XGA	106-1SD-1850-W	106-1SD-1850-WUX	106-1SD-2850-WUX	106-1SD-2850-WUX
NSN					
Screen Size					
Diagonal	75" 190.5 cm	85" 216 cm	85" 216 cm	75" 190.5 cm	75" 190.5 cm
# of Display Areas	1	1	1	2	3
WxH	5' x 3.8' 1.52 x 1.16 m	6' x 3.8' 1.82 x 1.16 m	6' x 3.8' 1.82 x 1.16 m	10.3' x 4.1' 3.14 x 1.25 m	15.3' x 4.1' 4.66 x 1.25 m
Weight	107 lbs 48.6 kg	131 lbs 59.4 kg	141 lbs 64 kg	216 lbs 98 kg	266 lbs 120.7 kg
Dimensions					
Stowed	61" x 17.5" x 16.8" 154.9 x 44.5 x 42.7 cm	61" x 17.5" x 16.8" 54.9 x 44.5 x 42.7 cm	61" x 17.5" x 16.8" 54.9 x 44.5 x 42.7 cm	61" x 17.5" x 16.8" 54.9 x 44.5 x 42.7 cm	61" x 17.5" x 16.8" 54.9 x 44.5 x 42.7 cm
Deployed	60" x 62" x 91" 152.4 x 157.5 x 231.1 cm	74" x 60" x 91" 188 x 152.4 x 231.1 cm	74" x 60" x 96" 188 x 152.4 x 243.8 cm	124" x 60" x 91" 315 x 152.4 x 231.1 cm	184" x 60" x 91" 467.4 x 152.4 x 231.1 cm
Display Resolution	1024 x 768 (XGA)	1200 x 800 (WXGA)	1920 x 1200 (WUXGA)	1920 x 1200 (WUXGA)	1920 x 1200 (WUXGA)

Products, product specifications and data are subject to change without notice to improve reliability, function, and/or design. Please contact Customer Service at 800.969.8527 for the most up-to-date product information.







HDT Expeditionary Systems, Inc.

30500 Aurora Road, Suite 100 Solon, OH 44139 USA P 800.969.8527 / 540.887.4700 sales@hdtglobal.com