## HDT DRASH<sup>®</sup> M SERIES SHELTERS

Shelters from 442 to 748 ft<sup>2</sup> (41 to 69.5 m<sup>2</sup>) of Usable Space





Widest of the man-portable HDT DRASH military tents, the DRASH M Series shelter is a mobile, lightweight, rugged, reliable and user-friendly soft-walled shelter solution perfect for command post or medical applications.

M Series shelters provide an interior width of 18 feet and can be lengthened to increase an operating area by removing shelter end sections and adding additional center sections. The M Series shelters come in three basic models in varying lengths.

All M Series shelters can be easily set up or struck within minutes with 4 to 6 people. The shelters do not require any special equipment for either setup or striking. Simply offload and position, spread and lift, attach end caps and secure.

M Series shelters pack down to less than 2% of deployed size for easy transport. Additionally, M Series tents can be integrated with HDT Utility Support Transport (UST) Trailers to allow for a complete power and mobility package that ensures optimal operations in extreme weather conditions.

M Series Shelters have undergone extensive testing at the Army's Aberdeen Test Center and include rugged, reliable materials to hold up even under the toughest conditions (wind, rain, snow load, blackout and UV).

All M Series Shelters include center sections, end caps, windows, doors, flooring, a steel stake pin set, a repair kit, push poles and a transport bag. Additionally, the 748 ft<sup>2</sup> M Series shelter includes a plenum. An optional Maintenance Door is available allowing smaller UAV's or vehicles access into the tent for maintenance or storage purposes.

## **KEY FEATURES**

- Unique design no loose parts or pieces to assemble or misplace
- Set up and strike by as few as four to six people within minutes
- Packs down to an average of less than 2 % of deployed size
- Networks with other HDT Shelters for maximum footprint flexibility
- Operable temperature range: -50°F to 131°F (-45.5°C to 55°C)
- Meets all U.S. Military requirements for soft-walled shelters
- Optional EMI liner available

Shelters from 442 to 748 ft² (41 to 69.5 m²) of Usable Space

## GLOBAL


## HDT DRASH M SERIES SHELTER SPECIFICATIONS

Ordering information	MX	MX5	M
Available colors			
Olive Drab			
Part number	MXA2000G	SH201-0601G	MA100100
NSN	8340-01-538-1822	8340-01-540-7566	8340-01-533-1654
On GSA Contract	N/A	N/A	N/A
Tan			
Part number	MXA2000T	SH201-0601T	MA100500
NSN	8340-01-538-1823	8340-01-540-7592	8340-01-533-1653
On GSA Contract	N/A	N/A	N/A
Dimensions			
Floor space	18' x 29.1' / 5.5 x 8.9 m	18' x 33.3' / 5.5 x 10.1 m	18' x 46' / 5.5 x 14 m
Area			
Entire shelter	442 ft <sup>2</sup> / 41 m <sup>2</sup>	519 ft² / 48.2 m²	748 ft <sup>2</sup> / 69.5 m <sup>2</sup>
Center section	306 ft <sup>2</sup> / 28 m <sup>2</sup>	383 ft <sup>2</sup> / 36 m <sup>2</sup>	612 ft <sup>2</sup> / 57 m <sup>2</sup>
Individual endcap**	68 ft² / 6.3 m²	68 ft <sup>2</sup> / 6.3 m <sup>2</sup>	68 ft <sup>2</sup> / 6.3 m <sup>2</sup>
Exterior (L x W x H)	30.7' x 19.8' x 11.1' / 9.4 x 6 x 3.4 m	34.9' x 19.8' x 11.1' / 10.6 x 6 x 3.4 m	47.7' x 19.8' x 11.1' / 14.5 x 6 x 3.4 m
Packed Dimensions			
Center section only*	56" x 44.5" x 31.5"	56" x 44.5" x 33.5"	56" x 44.5" x 31.5"
	142 x 113 x 80 cm	142 x 113 x 85.1 cm	142 x 113 x 80 cm
Individual endcap**	51" x 23" x 23"	51" x 23" x 23"	51" x 23" x 23"
	130 x 58 x 58 cm	130 x 58 x 58 cm	130 x 58 x 58 cm
Weight			
Entire shelter	625 lbs / 283.5 kg	724 lbs / 328.4 kg	1,115 lbs / 506 kg
Center section only*	490 lbs / 222.3 kg	590 lbs / 267.3 kg	980 lbs / 443.9 kg
Individual endcap**	67 lbs / 30.4 kg	67 lbs / 30.4 kg	67 lbs / 30.4 kg
Set-Up			
Time	< 15 minutes	< 15 minutes	< 15 minutes
Personnel	4 – 6 each	4 – 6 each	4 – 6 each

\*The DRASH<sup>™</sup> M Shelter includes two center sections, which are stored in two separate packages. Measurements reflect individual packages. \*\*Two per shelter. Maintenance doors also available.

Products, product specifications and data are subject to change without notice to improve reliability, function, and/or design. Please contact Customer Service at 800.969.8527 for the most up-to-date product information.





NON-EXPORT CONTROLLED INFORMATION

Revision 6 03-23 01-01-01-0349