

HDT QUICK HALT / TAC SHELTER

Our Lightest, Fastest Shelter System



The Quick Halt / TAC Shelter from HDT meets the U.S. Military's need for a truly rapid, forward-deployed shelter. Perfect for Company-Brigade level operations, the Quick Halt / TAC shelter is purpose-built to help warfighters jump fast and often to avoid detection.

Available in multiple sizes, Quick Halt / TAC shelter can be complexed or booted to a vehicle to give a command element additional space. The shelter includes a fabric floor, interior liner with wire harness, ECU ports and power cable passthrough.

Using combat-proven mil-spec design and materials and HDT's articulating frame technology constructed from Titanite® components. Titanite provides 270 percent more flex strength than aluminum for the same diameter and cross-sectional area, resulting in a lightweight and cost-effective solution that reduces the logistical burden associated with legacy shelters.

KEY FEATURES

- Complexing door to door or shelter open end can be done without additional boots, frame, or fabric components
- Light fixture hanging rings
- Interior liner assists with temperature regulation
- Withstands 55 mph sustained wind
- Quick Halt/TAC Includes:
 - Fabric floor
 - Interior Liner with wire harness
 - ECU ports, power cable passthrough on end walls
 - Steel stake kit with mallet
 - Repair Kit
 - Pre-attached wind lines



HDT QUICK HALT / TAC SHELTER

Our Lightest, Fastest Shelter System



Ordering information	Model 402	Model 403
Tan		
HDT part number	101-H041605-130	101-H040763-130
NSN	N/A	N/A
Olive Drab		
HDT part number	101-H041605-120	101-H040763-120
NSN	N/A	N/A
Interior dimensions		
Floor space	12' x 15' 3.66 x 4.57 m	15' x 18' 4.57 x 5.49 m
Area	180 ft ² 16.7 m ²	270 ft ² 25.1 m ²
Door information	End-wall doors	End-wall and side doors
Packed dimensions	75" x 26" x 22" 190.5 x 66 x 55.9 cm	75" x 32" x 28" 190.5 x 81.3 x 71 cm
Weight	227 lbs 103 kg	295 lbs 134 kg
Set-up		
Time	3-5 minutes	4-7 minutes
Personnel	2 each	2 each

Products, product specifications and data are subject to change without notice to improve reliability, function, and/or design. Please contact Customer Service at 800.969.8527 for the most up-to-date product information.



HDT Expeditionary Systems, Inc.

30500 Aurora Road, Suite 100, Solon, OH 44139 USA
P 800.969.8527 / 216.HDT.6111 / sales@hdtglobal.com

NON-EXPORT CONTROLLED INFORMATION

Revision 03 07-23 01-01-01-0561